



## Microline Dot Matrix Printers

### ML3320 ML3321 9-Pin Dot Matrix Printer

#### High performance, versatile printer for dedicated forms printing

The ML3320/ML3321 narrow and wide carriage printers are suited to high speed, high volume data and word processing applications where fast throughput and flexible paper management are required. Outstanding reliability, ease-of-use and barcoding facilities make them ideal for customer service points in wholesale, retail and service environments that produce applications.

#### Highlights:

- 80/136 column dot matrix printers
- High durability 9-pin print head
- Up to 435 characters per second print speed
- Multi-part paper-handling (original + 4 copies)
- Wide carriage (ML3321) ideal for accounts applications



## ML3320/ML3321

		ML3320	ML3321
General	Number of pins	9	
	No. of multi-part forms	5 (one original + 4 copies)	
Speed and throughput	Super speed (12cpi)	435cps	
	High speed draft (12cpi & 10cpi)	387cps	
	Utility (12cpi & 10cpi)	290cps	
	Near letter quality (12cpi & 10cpi)	73cps	
	Fastest print speed	435cps	
Font & print features	Carriage width (10cpi)	80 columns	136 columns
	Max. in compression mode	160 columns	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 240 x 216 dpi	
	Typeface & Font	NLQ-Courier (Scalable), NLQ-Gothic (Scalable), OCR-B, High Speed Draft, Utility + Barcodes	
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore	
Emulations & Interfaces	Printer emulations	Epson FX, IBM ProPrinter/Graphics, Oki MicroLine	
	Standard interfaces	Centronics Parallel + USB	
	Optional interfaces	Serial RS 232C/RS 422/Current Loop	
Paper handling	Continuous paper	76–254mm	76–406mm
	Continuous envelopes	165 x 91mm	239 x 102mm
	First printable line (from top of page)	8.9mm	
	Standard	Paper parking, Zero tear-off, Autoload single sheet, Push tractors, Bottom feed	
	Optional	Pull tractors, Single/dual bin cut-sheet feeder, Roll paper stand (ML3320 only), Bottom tractors with metal long-life tear-off bar	
Physical	Dimensions (HxWxD)	116 x 398 x 345mm	116 x 552 x 345mm
	Weight	6.5kg	8.5kg
	Memory	88KB	
	Noise level	57dB(A)/52dB(A) (quiet mode)	
Power	Power requirements	230V AC	
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	3 million characters in utility mode at 10cpi (re-inking cartridge)	
	MTBF	10,000 hours	

**Consumables Information:** Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

**OKI EUROPE LTD.**  
 Blays House, Wick Road  
 Egham, TW20 0HJ  
 United Kingdom  
 T +44(0) 20 8219 2190  
 F +44(0) 20 8219 2199  
[WWW.OKIPRINTINGSOLUTIONS.COM](http://WWW.OKIPRINTINGSOLUTIONS.COM)

**OKI**  
 PRINTING SOLUTIONS